

RECEIVED  
CENTRAL FAX CENTER

SEP 21 2006

## AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1 - 31. (Cancelled)

32. (Currently Amended) An apparatus comprising:

a silicon substrate;

a microresonator disposed on the silicon substrate, the microresonator having an annular structure to recirculate light at a desired wavelength, the microresonator including [[one or more of]] nanocrystals in a matrix; and

[[a pump]] an LED disposed [[vertical]] vertically relative to the microresonator to excite recirculation of light in the microresonator.

33. (Previously Presented) An apparatus as claimed in claim 32, further comprising at least one patterned waveguide disposed on the silicon substrate wherein light may be coupled between the microresonator and the waveguide.

34. (Previously Presented) An apparatus as claimed in claim 33, wherein the waveguide is above the microresonator.

35. (Previously Presented) An apparatus as claimed in claim 33, wherein the microresonator is coupled between two waveguides.

36. (Previously Presented) An apparatus as claimed in claim 32, wherein the annular structure is a ring.

Atty Docket No. 42P18458  
Application No. 10/749,986

2

BEST AVAILABLE COPY

37. (Previously Presented) An apparatus as claimed in claim 36, wherein the ring has a length from a center of the ring to a center of a waveguide that forms the ring being proportional to an integer multiple of a desired wavelength.

38. (Previously Presented) An apparatus as claimed in claim 32, wherein the annular structure is a disk.

39. (Previously Presented) An apparatus as claimed in claim 38, wherein the disk has a perimeter that is an integer multiple of a wavelength.

40. (Currently Amended) An apparatus as claimed in claim 32, wherein the nanocrystals comprise silicon and are included in at least one of [[silicon dioxide,]] silicon nitride, and alumino-silicate.

41. (Previously Presented) An apparatus as claimed in claim 32, wherein the microresonator includes one or more rare earth elements.

42. (Previously Presented) An apparatus as claimed in claim 41, wherein the one or more rare earth elements includes at least one of erbium and ytterbium.

43. (Currently Amended) An apparatus as claimed in claim 32, wherein the [[pump]] LED is [[above]] disposed on top of the microresonator.

44. (Currently Amended) An apparatus as claimed in claim 32, wherein the pump is able to tunnel current through the microresonator to form electron-hole pairs in the nanocrystals.

45. (Currently Amended) An apparatus comprising:  
  
a silicon substrate;

BEST AVAILABLE COPY

a microresonator disposed on the silicon substrate, the microresonator having an annular structure to recirculate light at a desired wavelength, wherein the microresonator includes silicon nanocrystals, silicon-germanium nanocrystals, or a combination thereof; [[and]] a patterned waveguide disposed [[vertically relative to]] above and optically coupled with the microresonator; and

a pump disposed above or below the microresonator to excite circulation of light in the microresonator.

46. (Previously Presented) An apparatus as claimed in claim 45, wherein a distance between the waveguide and the microresonator is equal to or less than 250 nanometers.

47. (Previously Presented) An apparatus as claimed in claim 45, further comprising a second waveguide optically coupled with the microresonator.

48. (Previously Presented) An apparatus as claimed in claim 45, wherein the annular structure is a ring having a length from a center of the ring to a center of a waveguide that forms the ring being proportional to an integer multiple of a desired wavelength.

49. (Previously Presented) An apparatus as claimed in claim 45, wherein the annular structure is a disk having a perimeter that is an integer multiple of a wavelength.

50. (Previously Presented) An apparatus as claimed in claim 45, wherein the microresonator includes one or more rare earth elements.

51. (Cancelled)

52. (Currently Amended) An apparatus as claimed in claim 45, [[further comprising a pump to excite circulation of light in the microresonator,]] wherein the pump is to tunnel

current through silicon dioxide to form electron-hole pairs in the nanocrystals in the silicon dioxide.

53. (Currently Amended) An apparatus as claimed in claim ~~[[32]]~~ 45, wherein the pump comprises an LED.

54. (Previously Presented) An apparatus as claimed in claim 53, wherein the LED emits light at a wavelength that is less than 900 nanometers.

55. (Cancelled)

56. (Previously Presented) The apparatus as claimed in claim 45, wherein the patterned waveguide includes material deposited on the silicon substrate.

57. (Currently Amended) An apparatus comprising:

a silicon substrate;

a microresonator disposed on the silicon substrate, the microresonator having an annular structure to recirculate light at a wavelength, the microresonator including nanocrystals comprising silicon in an Al-SiO<sub>x</sub> matrix; and

a patterned waveguide optically coupled with the microresonator.

58. (Previously Presented) The apparatus of claim 57, wherein the patterned waveguide is positioned vertically relative to the microresonator.

59. (Previously Presented) The apparatus of claim 57, further comprising a pump positioned vertically relative to the microresonator to excite recirculation of light in the microresonator.

60. (Previously Presented) The apparatus of claim 57, further comprising an LED to excite recirculation of light in the microresonator.

61. (New) The apparatus of claim 57, wherein the nanoparticles comprise one or more selected from silicon particles and silicon-germanium particles.

[[61.]] 62. (New) The apparatus of claim 32, wherein the LED comprises a low power LED.

BEST AVAILABLE COPY